## Long-Lasting Radial For Trailer Towing

- Helps make trailer towing easier, more stable and more economical
- Sizes available for boat trailers, 5th wheel trailers, travel trailers and pop-up campers
- Delivers dependable highway stability, positive traction and long-lasting wear

| TIRE SIZE | LOAD RANGE | SPEED RATING | TREAD DEPTH (32s) | APPRVD. RIM WIDTHS | MEAS. RIM WIDTH | NEW TIRE WIDTH | OUTSIDE DIAMETER | TREAD WIDTH | STATIC LOADED RADIUS | REVS PER MILE | MAX. LOAD AT INFLA. (PSI)SINGLE |
|---|---|---|---|---|---|---|---|---|---|---|---|
| ST175/80R13 | B | 65 | 9 | 4.5 - 5.5 | 5.00 | 7.0 | 24.0 | 4.9 | 10.6 | 870 | 1100@35 |
| ST175/80R13 | C | 65 | 9 | 4.5 - 5.5 | 5.00 | 7.0 | 24.0 | 4.9 | 10.6 | 870 | 1360@50 |
| ST185/80R13 | C | 65 | 9 | 4.5 - 6.0 | 5.00 | 7.2 | 24.7 | 5.2 | 10.8 | 851 | 1480@50 |
| ST205/75R14 | B | 65 | 10 | 5.0 - 6.5 | 5.50 | 8.0 | 26.1 | 5.6 | 11.6 | 800 | 1430@35 |
| ST205/75R14 | C | 65 | 10 | 5.0 - 6.5 | 5.50 | 8.0 | 26.1 | 5.6 | 11.6 | 800 | 1760@50 |
| ST205/75R14 | C | 65 | 10 | 5.0 - 6.5 | 5.50 | 8.0 | 26.1 | 5.6 | 11.6 | 800 | 1760@50 |
| ST215/75R14 | C | 65 | 10 | 5.5 - 7.0 | 6.00 | 8.5 | 26.7 | 6.0 | 11.8 | 783 | 1870@50 |
| ST215/75R14 | C | 65 | 10 | 5.5 - 7.0 | 6.00 | 8.5 | 26.7 | 6.0 | 11.8 | 783 | 1870@50 |
| ST205/75R15 | B | 65 | 9 | 6.0 - 6.5 | 5.50 | 8.0 | 27.1 | 5.6 | 12.0 | 770 | 1480@35 |
| ST205/75R15 | C | 65 | 9 | 6.0 - 6.5 | 5.50 | 8.0 | 27.1 | 5.6 | 12.0 | 770 | 1820@50 |
| ST225/75R15 | C | 65 | 10 | 6.0 - 7.0 | 6.00 | 8.8 | 28.3 | 6.2 | 12.5 | 738 | 2150@50 |
| ST225/75R15 | D | 65 | 10 | 6.0 - 7.0 | 6.00 | 8.8 | 28.3 | 6.2 | 12.5 | 738 | 2540@65 |
| ST235/80R16 | D | 65 | 9 | 6.0 - 7.5 | 6.50 | 9.25 | 30.8 | 6.0 | N/A | 673 | 3000@65 |

*Fabric/Steel Construction*

BOAT TRAILER, 5TH WHEEL, TRAVEL TRAILER,POP-UP CAMPER